

# Seismic Wavefield Imaging in the Tokyo Metropolitan Area Based on the Replica Exchange Monte Carlo Method

Hiromichi Nagao

*Earthquake Research Institute, The University of Tokyo, Japan  
Graduate School of Information Science and Technology, The University of Tokyo, Japan*

Masayuki Kano, Shin-ichi Ito, Shin'ichi Sakai, Shigeaki Nakagawa, Muneo Hori, Naoshi Hirata

*Earthquake Research Institute, The University of Tokyo, Japan*

Kenji Nagata

*Artificial Intelligence Research Center, National Institute of Advanced Industrial Science and Technology, Tokyo, Japan  
Presto, Japan Science and Technology Agency, Saitama, Japan*

Long-period ground motions due to large earthquakes can cause devastating disasters, especially in urbanized areas located on sedimentary basins. To assess and mitigate such damage, it is essential to rapidly evaluate seismic hazards for infrastructures, which can be simulated by seismic response analyses that use waveforms at the base of each infrastructure as an input ground motion. The present study reconstructs the seismic wavefield in the Tokyo metropolitan area located on the Kanto sedimentary basin, Japan, from seismograms of the Metropolitan Seismic Observation network (MeSO-net). The obtained wavefield fully explains the observed waveforms in the frequency band of 0.10–0.20 Hz. This is attributed to the seismic wavefield imaging technique proposed by Kano *et al.* [Geophys. J. Int., 2017], which implements the replica exchange Monte Carlo method to simultaneously estimate model parameters related to the subsurface structure and source information. Further investigation shows that the reconstructed seismic wavefield lower than 0.30 Hz is of high quality in terms of variance reduction, which quantifies a misfit in waveforms, but that the variance reduction rapidly worsens in higher frequencies. Meanwhile, the velocity response spectra show good agreement with observations up to 0.90 Hz in terms of the combined goodness-of-fit, which is a measure of misfit in the velocity response spectra. Inputting the reconstructed wavefield into seismic response analyses, we can rapidly assess the overall damage to infrastructures immediately after a large earthquake.

## Acknowledgments

This research was supported by the Special Project for Reducing Vulnerability for Urban Mega Earthquake Disasters from the Ministry of Education, Culture, Sports, Science, and Technology of Japan.